



# महोत्तरी गाउँपालिका गाउँ कार्यपालिकाको कार्यालय

महोत्तरी, महोत्तरी



मधेश प्रदेश, नेपाल

पत्र संख्या :- २०८२/८३

चलानी नं :-

मिति : २०८३/०९/१४ गते

(प्रथम पटक प्रकाशन)

आ.व. २०८२/०८३ को इलेक्ट्रोनिक सामानहरूको खरिदका लागि बाजार दररेट प्रति ईकाइ मूल्य पेश गर्नु हुन सम्बन्धि सूचना ।

उपरोक्त सम्बन्धमा यस कार्यालयबाट देहायका इलेक्ट्रोनिक सामानहरूको लागत इस्टिमेट तयार गरि खरिद गर्नु पर्ने भएकोले तपसिलमा उल्लेखित इलेक्ट्रोनिक सामानहरूको उचित बाजार दररेट यो सूचना प्रकाशन भएको मितिले ०७ दिनभित्र प्रति ईकाइ मूल्य खुलाई यसै साथ माग गरिएको आवश्यक कागजातहरू संलग्न गरी कार्यालयमा पेश गर्नुहुन अनुरोध गरिन्छ ।

पेश गर्नुपर्ने कागजातहरू:

१. फर्म दर्ता प्रमाणपत्रको प्रतिलिपि (म्याद ननाघेको)
२. मू.अ.कर दर्ता प्रमाणपत्रको प्रतिलिपि
३. प्रति ईकाइ खुलाई दर उल्लेख गरेको कागजात

नोट:-

१. यस सूचनामा मिल्ने इलेक्ट्रोनिक सामानहरूको दररेट मात्र पेश गर्नुपर्नेछ।
२. मू.अ.कर बाहेक दररेट उल्लेख गर्नुपर्नेछ ।

यस सूचनासंग संलग्न सामग्रीहरूको तालिकामा उल्लेख भए अनुसारको दररेट उल्लेख गरेर हरेक पानामा हस्ताक्षर र फर्मको छापसहित बुझाउनु पर्नेछ।


तपसिल


S.N.	Device Description	Specification	Unit /Quantity
1	4MP Colourview Bullet Network Camera	4MP ColorVu Smart Hybrid Light Camera with 1/3" progressive CMOS sensor, delivering 2560×1440 resolution at 30fps. Supports H.265+/H.264 compression, DWDR, 3D DNR, and BLC. Features up to 30m light range, built-in microphone, PoE/DC12V power options.	1 / Pcs

*(Signature)*  
प्रमुख



14	16 Gigaport Poe Switch	2 Uplink 16 Port PoE Switch unmanaged design with 16×1000M PoE ports and 2×1000M uplink ports. Supports IEEE 802.3af/at standards, 35W PoE power budget, up to 300m transmission distance, reliable data transfer, and built-in 6KV surge protection for enhanced network safety and stability.	1 / Pcs
15	Power Extension Board	6-port (6 socket) power extension board—also called a power strip—typically follows standard electrical and safety specifications. Here's a clear, practical specification overview based on common products	1 / Pcs
16	Camera Installation Materials	Other Materials for Cammera installation .	Per Camera
17	Camera Installation Charge	Installation and Configuration Charge	Per Camera
18	All in One Computer	Intel Core i5-1334U Processor (10 Cores, 1.30/4.60 GHz CPU, 12MB Cache Memory), Intel UHD Graphics, 8GB DDR4 RAM (Upgradable to 16GB*2), 512 GB M.2 2280 PCI-E Gen 4 SSD (Supports up to 1TB), 23.8" FHD (1920 x 1080) IPS Display, Windows 11, MS Office 2024, 5.0 MP HD Webcam	1 / Pcs
19	Projector	Resolution 800 × 600 (SVGA); brightness 4,000 ANSI lumens; color depth approximately 1.07 billion colors (10-bit/30-bit); lamp power around 200–270W; contrast ratio up to 25,000:1; aspect ratio 4:3 (supports 16:9/16:10); lamp life up to 15,000 hours ; built-in speaker; vertical keystone correction; projection size up to around 300 inches; connectivity ports including PC in (D-sub 15-pin) ×1, monitor out (D-sub 15-pin) ×1, composite video in (RCA) ×1, S-Video in (Mini DIN 4-pin) ×1, HDMI ×2 (version 1.4a/HDCP 1.4), USB Type-A ×1, USB Mini-B ×1, and RS-232 (DB-9 pin) ×1; compatible with multiple video input formats up to Full HD	1 / Pcs
20	Projector Screen	4:3 aspect ratio; diagonal size: 0.42 mm matte white fabric (Grade-B); mount type: wall and ceiling mountable; projection type: front projection; gain: matte white fabric (Grade-B); screen surface: white fabric; viewable height: 90 inches; viewable width: 120 inches	1 / Pcs
21	Projector Ceiling Mount	loading capacity: 25 kg; height adjustable projector mount; suitable for ceiling mounting and projector hanging applications; construction material: aluminum and cold-rolled precision seamless steel tubes	1 / Pcs
22	Projector Installation Charge	Installation and Configuration Charge	Per Projector

  
.....  
(राकेश कुमार झा)  
सूचना प्रविधि अधिकृत



2	4 Mp Dome Network Camera	4MP Dome Network Camera with 1/2.8" progressive CMOS sensor, delivering 1920×1080 resolution at 30fps. Supports H.265+/H.264 compression, DWDR, 3D DNR, and BLC. Features IR night vision up to 30m, durable dome design, PoE/DC12V power supply, weather resistance, and remote viewing via mobile app and software platform.	1 / Pcs
3	32 Channel NVR 4MP Support	32 CH NVR with AcuSense technology for smart detection and reduced false alarms. Supports up to 32 IP cameras, H.265+/H.264 formats, and 160 Mbps bandwidth. Offers efficient playback with AcuSearch, automatic camera setup, and decoding up to 12MP, 8MP, 4MP, or 1080p resolution streams.	1 / Pcs
4	Cat6 Cable Outdoor	305 m CAT6 Network Cable; Category: Cat.6; Sheath Printing: 75°C U/UTP CAT6 verified to ANSI/TIA-568C.2; PVC Standard: ISO/IEC 11801, ANSI/TIA-568-C.2, RoHS 2.0; Separator: Yes; Conductor Material: Solid bare copper (99.95%); Diameter: 0.55 ± 0.005 mm, 23 AWG; Insulation Material: HDPE; Insulation Diameter: 0.98 ± 0.05 mm.	1/Roll
5	8 TB Surveillance Harddisk	5400RPM BufferAmount-64MB,RoHScompatible Transfer Rate-145MB/s 64MB Cache, SATA 6Gb/s 23dBA, 300,000 unload cycles, 5400RPM	1 / Pcs
6	4 TB Surveillance Harddisk	5400RPM BufferAmount-64MB,RoHScompatible Transfer Rate-145MB/s 64MB Cache, SATA 6Gb/s 23dBA, 300,000 unload cycles, 5400RPM	1 / Pcs
7	PVC Box	PVC Box for installation.	1 / Pcs
8	Server Rack 6U	Can store NVR, Switch and other equipement	1 / Pcs
9	LED TV 32"	32" inch LED backlit technology with full HD 1920 x 1080 32" LED backlight monitor, 16.7 million colors display images perfectlyMultiple interfaces: HDMI, VGA, audio in ,Built-in speakerWide viewing angle: Horizontal 178°, Vertical 178° ,24/7 operationLED backlit technology with full HD 1920×1080 ,16.7 million color, display picture perfectly, HDMI support up to 1080P ,Multiple inputs: HDMI, VGABuild-in speaker, Audio 5W*2 ,Auto signal input Detection ,Smart engine for Phase/Image position/Color calibration.	
10	LED TV 43"	43" inch LED backlit technology with full HD 1920 x 108043" LED backlight monitor, 16.7 million colors display images perfectlyMultiple interfaces: HDMI, VGA, audio in ,Built-in speakerWide viewing angle: Horizontal 178°, Vertical 178° ,24/7 operationLED backlit technology with full HD 1920×1080 ,16.7 million color, display picture perfectly, HDMI support up to 1080P ,Multiple inputs: HDMI, VGABuild-in speaker, Audio 5W*2 ,Auto signal input Detection ,Smart engine for Phase/Image position/Color calibration.	1 / Pcs
11	4 Port Poe Switch	L2, Unmanaged,4 x 10/100 Mbps Auto-MDIX Ports,4 100M PoE port, 1 100M,uplink port,IEEE 802.3at/af PoE Compliant PoE power budget 58W,4 kV Surge Protection,IEEE 802.3x Flow Control Support 1 Gbps Switching Fabric,448 Kbits RAM Data Buffer,Sturdy Metal Enclosure	1 / Pcs
12	8 Port Poe Switch	L2, Unmanaged,8 x 10/100 Mbps Auto-MDIX Ports,8 100M PoE port 1 100M uplink port,IEEE 802.3at/af PoE Compliant,PoE power budget 58W 4 kV Surge Protection,IEEE 802.3x Flow Control Support,1.8 Gbps Switching Fabric,1.25 Mbits RAM Data Buffer,Sturdy Metal Enclosure	1 / Pcs
13	8 Gigaport Poe Switch	2 Uplink 8 Port PoE Switch unmanaged design with 8×1000M PoE ports and 2×1000M uplink ports. Supports IEEE 802.3af/at standards, 35W PoE power budget, up to 300m transmission distance, reliable data transfer, and built-in 6KV surge protection for enhanced network safety and stability.	

Handwritten signature and official stamp at the bottom right corner of the page.